

# DYNA FLEX

# SEWER CLEANING

## SWR-BLU (BLUE)



**Recommended For:** Use on high pressure sewer cleaning equipment.

**Innercore:** Orange seamless polyester tube

**Reinforcement:** Braided high tensile synthetic fiber

**Cover:** Blue high abrasion and fungus resistant polyurethane

**Temperature Range:** -40 degrees F. to +122 degrees F.  
(-40 degrees C. to +50 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Minimum Burst Press.		Min. Bend Radius (In.)	Wgt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	BAR	PSI	BAR		
SWRBLU-2P-12	3/4	19.05	1.16	29.59	3000	207	7500	517	4	32.0
SWRBLU-2P-16	1	25.40	1.44	36.58	3000	207	7500	517	6	40.0

**DYNA FLEX, INC.**  
**7300 INDUSTRIAL PARK BLVD.**  
**MENTOR, OHIO 44060 U.S.A.**

PHONE: (440) 946-0719 TOLL FREE: (800) 525-8463 FAX: (440) 946-4620  
Web Site: [www.sewerjettinghose.com](http://www.sewerjettinghose.com) E-mail: sales@flexinc.com