

DYNA FLEX

SEWER CLEANING

SWRBLUE (BLUE) 3,000 PSI



Recommended For: Use on high pressure sewer cleaning equipment.

Inner Core: Bonded, orange seamless polyolefin tube

Reinforcement: Two braids of high tensile synthetic fiber

Cover: Bonded, blue high abrasion tear and weather resistant thermoplastic polyurethane, featuring an anti-stick additive for a snag resistant slick surface.

Temperature Range: -40 degrees F. to +122 degrees F.
(-40 degrees C. to +50 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Minimum Burst Press.		Min. Bend Radius (In.)	Wt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	Mpa	PSI	Mpa		
SWRBLUE-12	3/4	19.05	1.18	29.85	3,000	20.7	7,500	51.7	5	30
SWRBLUE-16	1	25.40	1.43	36.32	3,000	20.7	7,500	51.7	6	37
SWRBLUE-20	1-1/4	31.75	1.77	44.96	3,000	20.7	7,500	51.7	8	53

DYNA FLEX, INC.
7300 INDUSTRIAL PARK BLVD.
MENTOR, OHIO 44060 U.S.A.

PHONE: (440) 946-0719 TOLL FREE: (800) 525-8463 FAX: (440) 946-4620
Web Site: www.dynaflexinc.com E-Mail: sales@flexinc.com Rev H, Aug 11, 2015