

DYNA FLEX

SEWER JETTING SWRG (GREEN) 4,000 PSI



Recommended For: Use on high pressure sewer jetting equipment.

Inner Core: Neutral color seamless polyester tube

Reinforcement: High tensile synthetic fiber

Cover: Bonded green high abrasion mold and fungus resistant polyether-urethane, featuring an anti-stick additive for a snag resistant slick surface.

Temperature Range: -40 degrees F. to +150 degrees F.
(-40 degrees C. to +65 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Minimum Burst Press.		Min. Bend Radius (In.)	Wt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	Mpa	PSI	Mpa		
SWRG-02*	1/8	3.18	.31	7.75	4,000	27.6	10,000	68.9	3/4	3.4
SWRG-03*	3/16	4.76	.41	10.29	4,000	27.6	10,000	68.9	1	6.5
SWRG-A-04*	1/4	6.35	.485	12.32	4,000	27.6	10,000	68.9	1-1/4	6.7
SWRG-06	3/8	9.53	.72	18.29	4,000	27.6	10,000	68.9	2	14
SWRG-08	1/2	12.70	.84	20.34	4,000	27.6	10,000	68.9	3	16
SWRG-10	5/8	15.87	1.03	26.16	4,000	27.6	10,000	68.9	4	25

*Single braid

**DYNA FLEX, INC.
7300 INDUSTRIAL PARK BLVD.
MENTOR, OHIO 44060 U.S.A.**

PHONE: (440) 946-0719 TOLL FREE: (800) 525-8463 FAX: (440) 946-4620
Web Site: www.dynaflexinc.com E-Mail: sales@flexinc.com Rev I, Jan 18, 2016