

DYNA FLEX

SEWER CLEANING

SWROE (ORANGE) 2,500 PSI

Recommended For: Use on high pressure sewer cleaning equipment.

Inner Core: Orange seamless polyolefin tube.

Reinforcement: Two braids of high tensile synthetic fiber.

Cover: Bonded orange high abrasion mold and fungus resistant polyether-urethane, featuring an anti-stick additive for a snag resistant slick surface.

Temperature Range: -40 degrees F. to +150 degrees F.
(-40 degrees C. to +66 degrees C.)

| Hose No. | Part | Nominal I.D. | | Nominal O.D. | | Maximum Oper. Press. | | Minimum Burst Press. | | Min. Bend Radius | Wt. Per 100 Ft. (Lbs.) |
|----------|------|--------------|-------|--------------|-------|----------------------|-----|----------------------|-----|------------------|------------------------|
| | | In. | mm. | In. | mm. | PSI | Bar | PSI | Bar | | |
| SWROE-12 | | 3/4 | 19.05 | 1.18 | 29.85 | 2,500 | 172 | 6,250 | 431 | 5 | 29 |
| SWROE-16 | | 1 | 25.40 | 1.43 | 36.32 | 2,500 | 172 | 6,250 | 431 | 6 | 40 |
| SWRO-20 | | 1-1/4 | 31.75 | 1.79 | 45.47 | 2,500 | 172 | 6,250 | 431 | 8 | 60 |