

DYNA FLEX

SEWER CLEANING

SWRO & SWROE (ORANGE) 2,500 PSI



Recommended For: Use on high pressure sewer cleaning equipment.

Inner Core: Bonded orange seamless polyolefin tube

Reinforcement: Two braids of high tensile synthetic fiber

Cover: Bonded orange high abrasion tear and weather resistant thermoplastic polyurethane, featuring an anti-stick additive for a snag resistant slick surface.

Temperature Range: -40 degrees F. to +122 degrees F.
(-40 degrees C. to +50 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Minimum Burst Press.		Min. Bend Radius (In.)	Wt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	Mpa	PSI	Mpa		
SWROE-12	3/4	19.05	1.18	29.85	2,500	17.2	6,250	43.1	5	30
SWROE-16	1	25.40	1.43	36.32	2,500	17.2	6,250	43.1	6	37
* SWRO-20	1-1/4	31.75	1.79	45.46	2,500	17.2	6,250	43.1	8	59

* Polyester tube

DYNA FLEX, INC.
7300 INDUSTRIAL PARK BLVD.
MENTOR, OHIO 44060 U.S.A.

PHONE: (440) 946-0719 TOLL FREE: (800) 525-8463 FAX: (440) 946-4620
Web Site: www.dynaflexinc.com E-Mail: sales@flexinc.com Rev G, Sept. 24, 2015