

DYNA FLEX INC. **SEWER CLEANING HOSE**
SWRO (ORANGE)



Recommended For: Use on high pressure sewer cleaning equipment.

Innercore: Orange seamless polyester tube

Reinforcement: Two braid high tensile synthetic fiber

Cover: Bonded, High Abrasion & Fungus Resistant Orange Polyurethane
 Featuring a Snag Resistant Slicker Surface

Temperature Range: -40 degrees F. to +122 degrees F.
 (-40 degrees C. to +50 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Minimum Burst Press.		Min. Bend Radius (In.)	Wgt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	BAR	PSI	BAR		
SWRO-12	3/4	19.05	1.165	29.59	2,500	172	6,250	431	4	32.0
SWRO-16	1	25.40	1.44	36.58	2,500	172	6,250	431	6	40.0
SWRO-20	1-1/4	31.75	1.80	45.72	2,500	172	6,250	431	8	59.0

DYNA FLEX, INC.
7300 INDUSTRIAL PARK BLVD.
MENTOR, OHIO 44060 U.S.A.

PHONE: (440) 946-0719 TOLL FREE: (800) 525-8463 FAX: (440) 946-4620
 Web Site: www.dynaflexinc.com E-Mail: sales@flexinc.com